

**WHAT IS CLAIMED IS:**

1. A method of forming an interlayer dielectric film in a semiconductor device, comprising the steps of:

5 forming an insulating film spacer only on the sidewall of conductive layer patterns at a region where a contact plug will be formed and then forming an interlayer dielectric film on the entire surface.

2. The method of forming an interlayer dielectric film in a semiconductor device as claimed in claim 1, wherein said conductive layer patterns are word lines or bit lines.

3. A method of forming an interlayer dielectric film in a semiconductor device, comprising the steps of:

15 forming conductive layer patterns of a given pattern and an insulating film spacer on the sidewalls of said conductive layer patterns through a common process;

removing said insulating film spacer formed in a region other than a region where a contact plug will be formed; and

20 forming an interlayer dielectric film on the entire surface.

4. The method of forming an interlayer dielectric film in a semiconductor device as claimed in claim 3, wherein said conductive layer patterns are word lines or bit lines.

5. A method of forming an interlayer dielectric film in a semiconductor device, comprising the steps of:

forming conductive layer patterns of a given pattern through a common  
5 process;

forming an interlayer dielectric film on the entire surface; and

removing said interlayer dielectric film at a region where a contact  
plug will be formed and then forming an insulating film spacer on the sidewall  
of said conductive layer patterns.

10

6. The method of forming an interlayer dielectric film in a semiconductor device as claimed in claim 5, wherein said conductive layer patterns are word lines or bit line.

15 7. A method of forming an interlayer dielectric film in a semiconductor device, comprising the steps of:

forming conductive layer patterns of a given pattern and an insulating  
film spacer on the sidewall of said conductive layer patterns through a  
common process;

20 burying a conductive material between said conductive layer patterns;  
removing said conductive material only at a given region and  
remaining said conductive material at remaining regions to form a contact  
plug; and

burying an interlayer dielectric film between said conductive layer

patterns at a region from which said conductive material is removed.

8. The method of forming an interlayer dielectric film in a semiconductor device as claimed in claim 7, wherein said conductive layer patterns are word lines or bit lines.